

NOELEX 25 KEEL WIRE INSTALLATION.

Noelex 25 Keel Wire Replacement Operation.

Noelex Yachts Australia Pty Ltd, recommend that you replace the keel wire in your Noelex 25 every two years, irrespective of its condition. This can be done with the boat on its trailer and is quite a simple operation.

- Step 1. Wind the keel down so that it rests on the trailer rollers. Remove the winch handle and winch cover plate. Also remove the inspection port.
- Step 2. Unbolt the winch and remove from the housing - you will have to unwind the wire from the drum as you go.
- Step 3. Unscrew and remove the aft pin on the keel, located inside the inspection port. (Do not remove the forward pin, as this will release the safety strop.)
- Step 4. With the pin removed, the wire can be withdrawn completely and unwound from the winch.
- Step 5. Attach the new wire to the winch drum in the same way as the old wire was attached.
- Step 6. Feed the thimble end of the wire (with the eye in it) down the aft hold on the top of the keel. Ensure that the pin goes back through the eye and screw it back up.
- Step 7. Rewind the wire onto the winch drum retaining as much tension as possible. Bolt the winch back in place - replace winch cover and inspection port, and the operation is complete.

-----  
The Keel Wire is available from Noelex Yachts Australia Pty Ltd or your nearest Dealer.

DIAGRAM OVER PAGE.

# NOELEX 25 KEEL INSTALLATION

